

Sdggmrss (T3000) / GATX type 9493

USAGE

This 6-axle double pocket wagon is suitable for the transportation of craneable semi-trailers (with steering axle) and mega-trailers, as well as swap bodies and ISO containers 20', 30', 40' and 45'.

PAYLOAD TABLE

| | А | В | С | D |
|----|--------|--------|--------|---------|
| S | 61.0 t | 73.0 t | 85.0 t | 100.0 t |
| SS | 61.0 t | 73.0 t | 85.0 t | 85.0 t |

PRODUCT DETAILS

| Tare weight | 35.0 t |
|---------------------|---------------|
| Loading weight | 100.0 t |
| Total weight | 135.0 t |
| Length over buffers | 34,200 mm |
| Loading length | 2 x 16,185 mm |









TECHNICAL DATA

| Loading length for semi-trailers between lateral beams | 10,490 mm |
|--|---------------|
| Loading width for semi-trailers between main girders | min. 2,700 mm |
| Saddle with 3 height adjustments (from the loading surface of the pocket): | |
| - lower position | 880 mm |
| - medium position | 980 mm |
| - upper position | I,130 mm |

REMARKS

- Interlocking of the kingpin with the support frame eliminates the need for wheel chocks and enables a safer and simpler loading of semi-trailers.

- Loading and unloading from top with crane or mobile handling device.
- The saddle is equipped with crash-elements.



#railcarleasingmadeeasier www.gatx.eu